





APS2050e

Electric vibratory plates

Excellent handling and maneuverability on soil and asphalt

The APS series is distinguished by its outstanding handling capabilities. Moving and turning these vibratory plates on fresh asphalt is unsurpassed in comfort and produces clean finishes with no marks. Even clean finishes at curbs are easy to produce due to the angular side edges of the base plate. The guide handle responds precisely to steering movements while still achieving low hand-arm vibrations of less than 5 m/s², which makes long and comfortable working conditions possible. Because of the direct drive, the APS series does not require V-belts and is therefore maintenance-free.

Highlights

- Starts with a push of a button
- Maintenance-free electric motor
- Removable battery
- Base plate optimized for perfect work results
- Excellent turning ability and control with simultaneously low HAV

Technical Data

Mechanical - Output Details

Centrifugal force	4,496 lbf
Area capacity	8,073.0 ft2/h
Gradeability	46.6 %
Standard Support Plate	without Support Plate
Mechanical Details	
Length Baseplate	23.6 "
Width	19.7 "
Width Baseplate	19.7 "
Height	26.1 "

Height Cover frame	26.1 "
Thickness Baseplate	0.4 "
Weight	191.14 lb
Ground clearance	26.1 "
Environment Data	
HAV summation (average value)	8.2 ft/s2
HAV summation (Standard)	EN 500-4
Electrical System	
Battery runtime	60.0 min